

Acoustic Fire Door Retainer

Trade Name: ASTRO DOORGARD RETAINER



- **Installs in under five minutes**
- **Improves access for wheelchair users**
- **Complies with BS EN 1155**
- **Automatically releases fire doors when the fire alarm sounds**
- **Available in a variety of colours**
- **Automatic night-time release facility**

30 or 60 Min Fire Rating

Description

Wedging open fire doors is illegal and dangerous.

Doorgard is the safe, legal and cost-effective solution for holding doors open.

The Doorgard provides a wire-free solution for legally holding open fire doors in any position. Suitable for normal environments, e.g. offices, care homes and hotels that have an automatic fire detection system installed.

Availability

Available to order in any quantity.

Colours : Black, Red, White ex stock. Other colours to minimum order.

To Order & Specify

Item	Price Unit	Colour	Product Code
Door Guard	1	Black	AFDGRBLK
Door Guard	1	Red	AFDGRRED
Door Guard	1	White	AFDGRWHT
Door Guard	1	Colour	AFDGRCOL

Please quote- Quantity / Trade name / Colour / Product Ref
 Typical wording- 10 / Astro Doorgard / Black / AFDGRBLK

Other colours P.O.A.

Test Reports

Dorgard 1328-A01 approvals and standards

BS EN 1155: 1997 building hardware.
Electrically powered hold-open devices for
swing doors. (Manufacturer's classification
number 357113.)

BS EN 50081-1: 1992 electro-magnetic
compatibility. Generic emission standard.

Residential, commercial and light industry.
BS EN 50082-1: 1997 electro-magnetic
compatibility. Generic immunity standard.
Residential, commercial and light industry.

USA patent number: 5525963
European patent number: 0635092

Health And Safety

The product does not present any known health hazards during or after installation. Normal good industrial and personal hygiene practises should be observed.

As part of our policy of ongoing improvements, we reserve the right to modify, alter or change product specifications without giving notice. Product illustrations are representations only. All information contained in this document is provided for guidance only, and as ASTROFLAME FIRESEALS LTD has no control over the installation methods of the products, or over the prevailing site conditions, no warranties expressed or implied are intended to be given as to the actual performance of the products mentioned or referred to, and no liability whatsoever will be accepted for any loss, damage or injury arising from the use of the information given of products mentioned or referred to herein.

The above information to the best of our knowledge is true and accurate and based upon current test data and is supplied for your guidance only. Customers should satisfy themselves to the suitability of the product in its intended use and no guarantee is given or implied since the conditions of actual use are beyond our control. ASTROflame (Fireseals) Ltd, disclaim any liability for loss, damage or other expense arising from the use of information, data or products mentioned or referred to and reserve the right to change any details or specifications without notice.

Astroflame (Fire Seals) Ltd. Intumescent House
Unit 8, The IO Centre, Stephenson Road, Segensworth
FAREHAM, ENGLAND PO15 5RU

tel 0800 023 2482
(01329 844500)

fax 0800 023 2483
(01329 844600)

intl
tel +44 1329 844500

fax +44 1329 844600

email