

Anti-Graffiti Paint

Trade Name ASTRO ANTI-GRAFFITI PAINT



ANTI GRAFFITI & ANTI FLY POSTING

MATT OR GLOSS FINISH

WASH OFF GRAFFITI WITH WATER



Description

A unique one-pack external coating designed to give effective protection against both graffiti and fly-poster attack. Astro Anti Graffiti Paint is a permanent not sacrificial system, allowing for repeated easy removal of any graffiti. Suitable for many surfaces, gives same day protection, repeat graffiti washes off with water.

Available in matt or gloss finish and has been specifically designed to minimise any alteration to the appearance of the protected surface.

This anti graffiti coating is suitable for a wide variety of surfaces. The matt version is particularly effective on the normally difficult to protect substrates such as rough brick or textured finishes.

The system can be used on concrete, render, masonry, porous stone, timber and previously painted surfaces, it should not however be used over Pliolite based products.

To test the suitability of Astro Anti Graffiti Paint we recommend a small trial application be carried out or contact Astroflame for advice.

Available in 5 or 20 litre tins.

To remove existing graffiti from surfaces see our

Application

Stir contents thoroughly before application.

Apply by brush roller or spray. If spraying take care not to contaminate surrounding property. Thin with up to 10% white spirit if needed.

Apply a minimum of two coats at the suggested spread rate to achieve optimum results.

For further advice contact Astroflame.

Typical Properties

- Appearance Semi-transparent/Clear Liquid
- Solvent White Spirit
- Viscosity 2.5 to 3 Poise
- Solids 34 to 36 % by Weight
- Specific Gravity 0.85 to 0.88
- Shelf Life 12 months in unopened container
- UV Resistance Excellent

Other Data :

- Supplied in 5 and 20 litre containers
- Spread rate 10 m² per litre, less on a porous substrate.
- Drying time 1 to 2 hours, depending on conditions
- Re-Coat interval 4 hours
- Application Temp' Minimum 4 °C
- Working Time Approx 30 to 90 mins.

Due to moisture curing nature of product do not leave in opened containers. Take care to clean equipment immediately after use.

To Order & Specify

ANTI GRAFFITI PAINT

PRODUCT REF	TYPE	SIZE
AAGPM5	MATT	5 LITRE
AAGPM20	MATT	20 LITRE
AAGPG5	GLOSS	5 LITRE
AAGPG20	GLOSS	20 LITRE

Packing

Single tins of 5 or 20 litre

To Order & Specify

Please quote- Quantity/Description / Product Code / Finish / Size eg:.

3 no Astro Anti Graffiti Paint / AAGPM5 / MATT / 5 LITRE

5 no Astro Anti Graffiti Paint / AAGPG20 / GLOSS / 20 LITRE

Health And Safety

Refer to _____ for this product.

As part of our policy of ongoing improvements, we reserve the right to modify, alter or change product specifications without giving notice. Product illustrations are representations only. All information contained in this document is provided for guidance only, and as ASTROFLAME FIRESEALS LTD has no control over the installation methods of the products, or of the prevailing site conditions, no warranties expressed or implied are intended to be given as to the actual performance of the products mentioned or referred to, and no liability whatsoever will be accepted for any loss, damage or injury arising from the use of the information given of products mentioned or referred to herein.

The above information to the best of our knowledge is true and accurate and based upon current test data and is supplied for your guidance only. Customers should satisfy themselves to the suitability of the product in its intended use and no guarantee is given or implied since the conditions of actual use are beyond our control. ASTROflame (Fireseals) Ltd, disclaim any liability for

loss, damage or other expense arising from the use of information, data or products mentioned or referred to and reserve the right to change any details or specifications without notice.

Astroflame (Fire Seals) Ltd. Intumescent House
Unit 8, The IO Centre, Stephenson Road, Segensworth
FAREHAM, ENGLAND PO15 5RU

tel 0800 023 2482
(01329 844500)

fax 0800 023 2483
(01329 844600)

intl
tel +44 1329 844500

fax +44 1329 844600

email