

---

## Trade Name: Astro FR Ceiling Valve

### Fire Rated Ceiling Air Valves

---

[COSHH Data](#)

[Installation Data](#)

[Product Images](#)

[Installation Video](#)

Fire rated ceiling air valves - supply and extract types.

Maintains integrity of fire rated ceilings for up to one hour.

Tested for 60 minutes to BS EN 1365-2

Meets the requirements of Building Regulations Document B

An alternative to more expensive metal Fire Rated Valves / Fire Dampers


Fits in the same way as a normal air valve

Air Flow is unaffected by fire resistant inserts

Easy to retro-fit in place of existing valves

Highly cost effective

Available in 80mm, 100mm, 125mm, 150mm and 200mm diameter in extract or supply versions.



---

### Description

---

The popularity of whole house ventilation and controlled ventilation is increasing. This results in an increased number of penetrations through fire compartment walls and floors producing open pathways for the passage of both smoke and fire.



Recessed ceiling air valves are now widely used in both domestic and commercial buildings. Ceilings must be fire protected in accordance with Approved Document B of the Building Regulations. Ceiling air valves, if left unprotected, allow a fire to spread rapidly through a building.

Once a hole is made in a ceiling for an air valve, the integrity of the construction and its ability to perform in a fire is reduced significantly. This opening must be firestopped to reinstate the original fire rating of the ceiling. Our fire rated ceiling air valve performs this fire stopping function when activated by the heat of a fire

If air valves are to be fitted to a ceiling where the downlights are fire rated then you need *fire rated ceiling air valves*.

Image to the left shows an activated ceiling valve .

## Availability

---

Item	Diameter	Product Ref
<b>EXTRACT VALVE - 60 Min Fire Rated</b>		
<b>SMALL</b>	<b>80mm</b>	<b>AFFRCV80E</b>
<b>MEDIUM</b>	<b>100mm</b>	<b>AFFRCV100E</b>
<b>LARGE</b>	<b>125mm</b>	<b>AFFRCV125E</b>
<b>X LARGE</b>	<b>150mm</b>	<b>AFFRCV150E</b>
<b>XX LARGE</b>	<b>200mm</b>	<b>AFFRCV200E</b>
<b>SUPPLY SIDE VALVE - 60 Min Fire Rated</b>		
<b>SMALL</b>	<b>80mm</b>	<b>AFFRCV80S</b>
<b>MEDIUM</b>	<b>100mm</b>	<b>AFFRCV100S</b>
<b>LARGE</b>	<b>125mm</b>	<b>AFFRCV125S</b>
<b>X LARGE</b>	<b>150mm</b>	<b>AFFRCV150S</b>
<b>XX LARGE</b>	<b>200mm</b>	<b>AFFRCV200S</b>

## Packing

---

All sizes - singles or packs of 10

## To Order & Specify

---

Please quote :  
QTY / TRADENAME / PRODUCT REF / SIZE

Typical wording:  
8no / Astro FR Ceiling Valve / AFFRCV125E - or - 2 packs / Astro FR Ceiling Valve / AFFRCV125S

## Fire Test or Assessment Reports

---

Successfully tested for 60 minutes according to BS EN 1365-2  
Test Report Number: IF10090 / Chiltern Fire

## Health and Safety

---

See COSHH Sheet.

## Installation

---

Please refer to our install sheet

As part of our policy of ongoing improvements, we reserve the right to modify, alter or change product specifications without giving notice. Product illustrations are representations only. All information contained in this document is provided for guidance only, and as ASTROFLAME FIRESEALS LTD has no control over the installation methods of the products, or of the prevailing site conditions, no warranties expressed or implied are intended to be given as to the actual performance of the products mentioned or referred to, and no liability whatsoever will be accepted for any loss, damage or injury arising from the use of the information given of products mentioned or referred to herein.

The above information to the best of our knowledge is true and accurate and based upon current test data and is supplied for your guidance only. Customers should satisfy themselves to the suitability of the product in its intended use and no guarantee is given or implied since the conditions of actual use are beyond our control. ASTROflame (Fireseals) Ltd, disclaim any liability for loss, damage or other expense arising from the use of information, data or products mentioned or referred to and reserve the right to change any details or specifications without notice.



Astroflame (Fire Seals) Ltd. Intumescent House  
Unit 8, The IO Centre, Stephenson Road, Segensworth  
FAREHAM, ENGLAND PO15 5RU

tel 0800 023 2482  
(01329 844500)

fax 0800 023 2483  
(01329 844600)

intl  
tel +44 1329 844500

fax +44 1329 844600

email [sales@astroflame.com](mailto:sales@astroflame.com)

[Homepage.](#)