

Trade Name: ASTRO DS DUCT SLEEVE

Intumescent Duct Sleeve

Duct sleeve with 2 hr rating to
BS 476 & EN 1366-3:2009

Uncapped / Uncapped (Open |
Open) fire tested as required for
ventilation systems.

Suitable for use through a wide
range of fire partition walls

Offers excellent acoustic
insulation



Maintains the thermal insulation
of the duct through the
penetration

Maintains vapour seal of existing
insulation

Sleeve can be easily fitted only
requiring access from one side

Allows the thermal movement of
the duct

Simple to install without special
tools or skills



Description

The ASTROflame range of Astro DS duct sleeves are intended for use where a ventilation duct passes through a fire rated wall. The sleeve maintains the integrity of the fire rated wall which would otherwise be lost.

In the event of a fire, the advanced Astro DS Duct Sleeve will expand with the heat, crushing the duct and closing off the hole to the fire for at least 2 hours **except the 220x90mm version which is rated 60mins.**

The Ventilation duct sleeves are available to fit all common sizes of plastic ventilation duct and are suitable for retro fitting with access only required from one side.

Availability

Astro DS Duct sleeves are currently available in the following nominal sizes:



Item	Width [mm]	Height [mm]	Length [mm]	Product Ref
Duct Sleeve	110	54	180	AFDS110
Duct Sleeve	204	60	180	AFDS204
Duct Sleeve	234	29	180	AFDS235
Duct Sleeve	308	29	180	AFDS308
Duct Sleeve Circular	-	103 Diam	150	AFDSC100X
Duct Sleeve Circular	-	127 Diam	280	AFDSC127X
Duct Sleeve Circular	-	159 Diam	180	AFDSC159X

Packed - Individually

To Order & Specify

Please quote- Quantity / Trade name / Product Ref / Size
Typical wording- 10 / Astro DS Duct Sleeve / AFDS204 / 204MM

Fire Tests

ASTROFLAME DS Duct Sleeves have undergone and passed testing in line with BS476 Part 22:1987 & BS EN 1366-3:2009 at Chiltern International Fire

Health and Safety

Refer to COSHH sheet

As part of our policy of ongoing improvements, we reserve the right to modify, alter or change product specifications without giving notice. Product illustrations are representations only. All information contained in this document is provided for guidance only, and as ASTROFLAME FIRESEALS LTD has no control over the installation methods of the products, or of the prevailing site conditions, no warranties expressed or implied are intended to be given as to the actual performance of the products mentioned or referred to, and no liability whatsoever will be accepted for any loss, damage or injury arising from the use of the information given of products mentioned or referred to herein.

The above information to the best of our knowledge is true and accurate and based upon current test data and is supplied for your guidance only. Customers should satisfy themselves to the suitability of the product in its intended use and no guarantee is given or implied since the conditions of actual use are beyond our control. ASTROflame (Fireseals) Ltd, disclaim any liability for loss, damage or other expense arising from the use of information, data or products mentioned or referred to and reserve the right to change any details or specifications without notice.

Astroflame (Fire Seals) Ltd. Intumescent House
Unit 8, The IO Centre, Stephenson Road, Segensworth
FAREHAM, ENGLAND PO15 5RU

tel 0800 023 2482
(01329 844500)

fax 0800 023 2483
(01329 844600)

intl
tel +44 1329 844500

fax +44 1329 844600

email sales@astroflame.com

[Homepage.](#)