

Product Data Sheet

Astro Coat - Spray Grade

Revision 5 - 28th January 2019



Astro Coat - Spray Grade

Ablative Coating

- CE Marked, UL-EU Listed & Certifire Approval.
- Fire Resistance Testing to EN 1366-3 : 2009.
- Fire Classification to EN 13501-2.
- Fire Resistance Testing to BS 476 Part 20 : 1987.
- Air Permeability testing to EN 1026.
- Acoustic Isolation testing to EN 10140.
- Remains flexible between -5°C to +40°C.
- Easy to use fibre free coating.
- Suitable for large openings in walls and floors with additional supports.
- Life expectancy of over 25 years.



Product Description

Astro Coat is a water-based, acrylic, ablative coating with excellent fire, water, air permeability and elastomeric properties.


It prevents the passage of fire, air and sound between fire rated compartments and has been tested in block wall, concrete, masonry, plasterboard partition and concrete floors.

Fire protects service penetration openings containing metallic pipes, cables, cable trays and trunking. Can be used to coat service insulation as part of the sealing system.

At normal temperatures the coating remains flexible to permit thermal and mechanical movement of services and the building structure.

Astro Coat is a thinner formulation for use with ASTRO BATT fire board, to seal the edges around the services and between the substrate and the batt before installation. Application is by spray, or brush or pouring applications. (Trowel Grade is also available).

Suitable for large openings in walls and floors with additional supports.

 1121
Astroflame Fireseals Ltd Unit 8 The I O Centre Stephenson Road Segensworth, Fareham Hampshire, PO15 5RU 14 1121-CPR-JA5026
ETA-14/0099 ETAG 026 – Part 1 ETAG 026 – Part 2 ASTRO BATT ASTRO COATING "see ETA-14/0099 for relevant characteristics"

Properties & Specification

Description	Water based flexible acrylic coating
Colour	White
Specific Gravity	1.25 – 1.3 g/cm ³
Fire Resistance/ Insulation	EN 1366-3 - EI 60, EI 90, EI 120, BS 476 240mins
Classification	EN 13501-2
Acoustic Insulation	EN 10140 49dB when installed with 50mm Astro Batt. EN 10140 63dB when installed with 2 x 50mm Astrol Batts & PB insert.
Air Permeability	600 Pa EN 1026 - 100Pa 1.8/1.4 m ³ /h/m ²
Shelf Life	12 Months
Cure Rate	0.5mm per day at 50% relative humidity 23°C
Tack Free	6 hrs at 23°C, 50% RH
Application Temperature	-5°C to +40°C
Coating Thickness	1mm Nominal, wet coating thickness

Product Availability

Astro Coat - Spray Grade - Sold per 5 Kilo Tub.

Product Code

Product Description

AFBCOAT5L	Astro Coat - Spray Grade
-----------	--------------------------

Compliance

Astro Coat is manufactured in the EU, meeting the highest quality standard in compliance to ISO EN 9001. For fire test certification and Technical advise contact Astroflame technical department.

To Order & Specify

Please contact us and quote the following information - Quantity / Product Code / Product Description
 Typical example:- 10 / AFBCOAT5L / Astro Coat

>> Tel: [01329 844 500](tel:01329844500) or >> Email: sales@astroflame.com

Installation

Please see installation sheet - This can be requested from our sales team T: [01329 844 500](tel:01329844500)
 or E: sales@astroflame.com

Health and Safety

Please see (SDS) Safety Data sheet - This can be requested from our sales team T: [01329 844 500](tel:01329844500)
 or E: sales@astroflame.com

As part of our policy of ongoing improvements, we reserve the right to modify, alter or change product specifications without giving notice. Product illustrations are representations only. All information contained in this document is provided for guidance only, and as ASTROFLAME FIRESEALS LTD has no control over the installation methods of the products, or of the prevailing site conditions, no warranties expressed or implied are intended to be given as to the actual performance of the products mentioned or referred to, and no liability whatsoever will be accepted for any loss, damage or injury arising from the use of the information given of products mentioned or referred to herein.

The above information to the best of our knowledge is true and accurate and based upon current test data and is supplied for your guidance only. Customers should satisfy themselves to the suitability of the product in its intended use and no guarantee is given or implied since the conditions of actual use are beyond our control. ASTROflame (Fireseals) Ltd, disclaim any liability for loss, damage or other expense arising from the use of information, data or products mentioned or referred to and reserve the right to change any details or specifications without notice.