

Product Data Sheet

Astro Putty

Revision 6 - 8th April 2019



Astro Putty

Fire Resistant Putty

- Fire Putty with fire resistance testing to EN 1366-3 EI 120, and BS 476 240mins.
- Fire Classification to EN 13501-2.
- Certifire 3rd Party Accreditation.
- Acoustic Isolation to EN 10140 to 65dB.
- Tested with metallic pipes and cables.
- Fills irregular shapes.
- Highly flexible and non-setting.
- Halogen free, resists fungi and vermin.



Certifire 3rd Party Accreditation

Product Description

Astroflame fire putty is a solvent free, easy to use, non-setting fire resistant compound, which is ideal for sealing around pipes and cables in walls and floors.

Tested to EN1366-3 on C1, C2 and D1 Type Cables and Metallic Pipes.

Causes no known detrimental effects to plastic pipes, plastic cables, sheathing or metallic components.

Can accommodate substantial movement of service penetrations.

The flexibility of the putty enables complex and irregular shapes and openings to be fire stopped.

Offers excellent hot and cold smoke sealing properties and is not affected by fungal attack or moisture.

Ideal for electrical, telecommunications and other such industries.

Astroflame fire putty has been independently tested in accordance with BS476: Part 20: 1987 and EN1366-3 and can provide up to 4 hours fire resistance depending on depth and volume.

Tested in block wall, concrete, masonry and plasterboard partition. Tested in concrete floors.

Specification

Colour	Neutral
Density	1.55 g/cm ³
Solids	82%
Shore A Hardness	50
Application temperature	+5°C to +45°C
Joint Movement	±10%
Fire Resistance	EN 1366-3 - EI 120 & BS476 - 240 mins

Product Availability

Product Code	Product Description	Size
AFIP	Astro Putty	1kg tubs.

To Order & Specify

Please contact us and quote the following information - Quantity / Product Code / Product Description / Size
 Typical example:- 12 / AFIP / Astro Putty / 1kg tub

>> Tel: [01329 844 500](tel:01329844500) or >> Email: sales@astroflame.com

Fire Test and Assessment Reports

Fire resistance testing to EN 1366-3 EI 120, and BS 476 240mins.
 Fire Classification to EN 13501-2.
 Certifire 3rd Party Accreditation.
 Acoustic Isolation to EN 10140 to 65dB.

Installation

Please see installation sheet - This can be requested from our sales team T: [01329 844 500](tel:01329844500)
 or E: sales@astroflame.com

Health and Safety

Please see (SDS) Safety Data sheet - This can be requested from our sales team T: [01329 844 500](tel:01329844500)
 or E: sales@astroflame.com

As part of our policy of ongoing improvements, we reserve the right to modify, alter or change product specifications without giving notice. Product illustrations are representations only. All information contained in this document is provided for guidance only, and as ASTROFLAME FIRESEALS LTD has no control over the installation methods of the products, or of the prevailing site conditions, no warranties expressed or implied are intended to be given as to the actual performance of the products mentioned or referred to, and no liability whatsoever will be accepted for any loss, damage or injury arising from the use of the information given of products mentioned or referred to herein.

The above information to the best of our knowledge is true and accurate and based upon current test data and is supplied for your guidance only. Customers should satisfy themselves to the suitability of the product in its intended use and no guarantee is given or implied since the conditions of actual use are beyond our control. ASTROflame (Fireseals) Ltd, disclaim any liability for loss, damage or other expense arising from the use of information, data or products mentioned or referred to and reserve the right to change any details or specifications without notice.